

- Electrostatic powder coating or anodized aluminum housing
- 5mm tempered glass
- Silicone seal with high protection level
- Corrosion resistant fittings
- Electrostatic painted aluminum injection assembly foot (adjustable for vertical-horizontal-angled mounting)
- 10kV lighting protective circuit
- Power and angle options for all pole types

## P W Product & Power Options

| Product Name | Light Color | Input Voltage (V) | Power (W) | Luminous Flux (lm) | Weight (kg) |
|--------------|-------------|-------------------|-----------|--------------------|-------------|
| SEYHAN       | NW          | 220-240V AC       | 45        | 6.290              | 4,4         |
| SEYHAN       | NW          | 220-240V AC       | 72        | 9.254              | 4,4         |

## S Driver Options

- 01 Standard Driver
- 06 DALI Driver

## O Lens Options




M3: Asymmetric Lens

## G Housing Color Options



## M Mounting Options



MK42: Ø42

MK60: Ø60

## Control System Options

| Color Type | PWM | INV PWM | DMX | DALI | 0-10V DC | NEMA Socket |
|------------|-----|---------|-----|------|----------|-------------|
| WW-NW-CW   |     |         |     | •    |          | •           |
| R,G,B,A    |     |         |     |      |          |             |
| RGB        |     |         |     |      |          |             |
| RGBA/W     |     |         |     |      |          |             |
| RGB DMX    |     |         |     |      |          |             |
| WHITE DMX  |     |         |     |      |          |             |



### Order Code

P . W . C . S . O . G . M

